
**Information technology — Radio
frequency identification for item
management —**

**Part 63:
Parameters for air interface
communications at 860 MHz to 960 MHz
Type C**

*Technologies de l'information — Identification par radiofréquence
(RFID) pour la gestion d'objets —*

*Partie 63: Paramètres de communications d'une interface radio entre
860 MHz et 960 MHz, Type C*



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	ix
Introduction.....	x
1 Scope	1
2 Conformance	1
2.1 Interrogator conformance and obligations.....	2
2.2 Tag conformance and obligations	2
3 Normative references.....	3
4 Terms and definitions, symbols and abbreviated terms.....	3
4.1 Terms and definitions	3
5 Symbols, abbreviated terms and notations.....	5
5.1 Symbols.....	5
5.2 Abbreviated terms	6
5.3 Notation	8
6 Type C.....	9
6.1 Parameter tables.....	9
6.2 Protocol overview.....	14
6.2.1 Physical layer.....	14
6.2.2 Tag-identification layer	14
6.3 Command types and command structure	14
6.3.1 General	14
6.3.2 Mandatory	15
6.3.3 Optional	15
6.3.4 Custom	15
6.3.5 Proprietary	15
6.4 Description of operating procedure	15
6.4.1 Signalling	15
6.4.2 Tag selection, inventory, and access.....	30
7 Battery Assisted Passive (BAP) Interrogator Talks First Type C systems (optional).....	78
7.1 Applicability	78
7.2 General overview, definitions, and requirements of BAP.....	78
7.3 Battery Assisted Passive inventoried flag and state machine behaviour modifications	80
7.3.1 Modification to ready state and power-down support for BAP Tags.....	80
7.3.2 Signal loss tolerance via timer (mandatory).....	81
7.3.3 Modified persistence of BAP PIE inventory flags (optional).....	83
7.4 Battery Assisted Passive PIE (optional)	85
7.4.1 <i>Flex_Query</i> command (optional)	85
7.4.2 BAP PIE detailed operation including optional Battery Saver Mode	86
7.5 Manchester mode Battery Assisted operation protocol extensions	92
7.5.1 Introduction.....	92
7.5.2 Physical layer.....	93
7.5.3 Manchester Activation	98
7.5.4 Commands summary	114
7.6 Extended Protocol Control and Battery Tag Capabilities Reporting and Setting	128
7.6.1 General	128
7.6.2 Extended Protocol Control definition.....	129
7.6.3 Battery Assisted Passive Tag Capability Reporting, Setting, and duty cycle/mode control (optional)	131
8 Sensor support	159

8.1	Applicability.....	159
8.2	Overview	159
8.3	Real Time Clock (RTC)	160
8.3.1	General.....	160
8.3.2	Setting the RTC	160
8.3.3	<i>BroadcastSync</i> command (optional, for Type C)	161
8.3.4	Time synchronisation.....	162
8.4	<i>HandleSensor</i> command (optional, for Type C)	163
8.5	Simple Sensor	164
8.5.1	Type C and Simple Sensor	164
8.6	Sensor Directory System and Full Function Sensors.....	166
8.6.1	Sensor Access – General Approach.....	166
Annex A	(normative) Extensible bit vectors (EBV).....	173
Annex B	(normative) State-transition tables	174
B.1	Contents	174
B.2	State transition tables for passive	174
B.2.1	Present state: Ready	174
B.2.2	Present state: Arbitrate	175
B.2.3	Present state: Reply	176
B.2.4	Present state: Acknowledged.....	177
B.2.5	Present state: Open	178
B.2.6	Present state: Secured.....	179
B.2.7	Present state: Killed	180
B.3	State transition tables for BAP PIE	181
B.3.1	Present state: sleep	181
B.3.2	Present state: low power listen	181
B.3.3	Present state: listen or stateful listen.....	181
B.3.4	Present state: stateful sleep or stateful low power listen	181
B.3.5	Present state: battery ready	182
B.3.6	Present state: Arbitrate	182
B.3.7	Present state: Reply	183
B.3.8	Present state: Acknowledged.....	184
B.3.9	Present state: Open	185
B.3.10	Present state: Secured.....	187
B.3.11	Present state: Killed	189
B.4	State transition tables for BAP Manchester.....	189
B.4.1	Present state: Hibernate	189
B.4.2	Present state: Activation code check.....	190
B.4.3	Present state: Stateful Hibernate	190
B.4.4	Present state: Battery Ready.....	191
B.4.5	Present state: Arbitrate	193
B.4.6	Present state: Reply	195
B.4.7	Present state: Acknowledged.....	197
B.4.8	Present state: Open	199
B.4.9	Present state: Secured.....	201
B.4.10	Present state: Killed	204
Annex C	(normative) Command-response tables.....	205
C.1	Contents	205
C.2	Command response tables for passive.....	205
C.2.1	Command response: Power-up.....	205
C.2.2	Command response: <i>Query</i>	205
C.2.3	Command response: <i>QueryRep</i>	206
C.2.4	Command response: <i>QueryAdjust</i>	206
C.2.5	Command response: <i>ACK</i>	207
C.2.6	Command response: <i>NAK</i>	207
C.2.7	Command response: <i>Req_RN</i>	207
C.2.8	Command response: <i>Select</i>	208
C.2.9	Command response: <i>Read</i>	208

C.2.10	Command response: <i>Write</i>	208
C.2.11	Command response: <i>Kill</i>	209
C.2.12	Command response: <i>Lock</i>	209
C.2.13	Command response: <i>Access</i>	210
C.2.14	Command response: <i>BlockWrite</i>	210
C.2.15	Command response: <i>BlockErase</i>	211
C.2.16	Command response: <i>BlockPermalock</i>	211
C.2.17	Command response: <i>T₂ timeout</i>	212
C.2.18	Command response: Invalid command.....	212
C.3	Command response tables for BAP PIE.....	213
C.3.1	Command response: <i>Flex_Query</i> (optional for BAP PIE).....	213
C.3.2	Command response: <i>INACT_T</i> or Selective Global Timeout.....	213
C.3.3	Command response: <i>Global Timeout</i>	214
C.3.4	Command response: <i>HandleSensor</i>	214
C.3.5	Command response: <i>BroadcastSync</i>	214
C.4	Command Response Tables for Manchester.....	215
C.4.1	Command response: <i>Power-up</i>	215
C.4.2	Command response: <i>QueryRep</i>	215
C.4.3	Command response: <i>QueryAdjust</i>	215
C.4.4	Command response: <i>ACK</i>	216
C.4.5	Command response: <i>NAK</i>	217
C.4.6	Command response: <i>Req_RN</i>	217
C.4.7	Command response: <i>Select</i>	217
C.4.8	Command response: <i>Read</i>	217
C.4.9	Command response: <i>Write</i>	217
C.4.10	Command response: <i>Kill</i>	217
C.4.11	Command response: <i>Lock</i>	217
C.4.12	Command response: <i>Access</i>	218
C.4.13	Command response: <i>BlockWrite</i>	218
C.4.14	Command response: <i>BlockErase</i>	218
C.4.15	Command response: <i>BlockPermalock</i>	218
C.4.16	Command response: <i>T₂ timeout</i>	218
C.4.17	Command response: <i>Long Activation</i>	218
C.4.18	Command response: <i>Short Activation</i>	219
C.4.19	Command response: <i>Query_BAT</i>	220
C.4.20	Command response: <i>Next</i>	221
C.4.21	Command response: <i>Deactivate_BAT</i>	221
C.4.22	Command response: <i>Broadcast ID</i>	222
C.4.23	Command response: <i>Multirate_Reset</i>	223
C.4.24	Command response: <i>HandleSensor</i>	223
C.4.25	Command response: <i>BroadcastSync</i>	223
C.4.26	Command response: <i>Session Flag timer timeout</i>	224
C.4.27	Command response: <i>INACT_T</i> or Selective Global Timeout.....	224
C.4.28	Command response: <i>Global Timeout</i>	224
C.4.29	Command response: <i>T_A</i>	225
C.4.30	Command response: <i>OpRegister Read/Write</i>	225
C.4.31	Command response: Invalid command.....	226
Annex D	(informative) Example slot-count (<i>Q</i>) selection algorithm.....	227
D.1	Example algorithm an Interrogator might use to choose <i>Q</i>	227
Annex E	(informative) Example of Tag inventory and access.....	228
E.1	Example inventory and access of a single Tag.....	228
Annex F	(informative) Calculation of 5-bit and 16-bit cyclic redundancy checks.....	232
F.1	Example CRC-5 encoder/decoder.....	232
F.2	Example CRC-16 encoder/decoder.....	232
F.3	Example CRC-16 calculations.....	233
Annex G	(normative) Dense- and Multiple-Interrogator channelised signalling.....	234
G.1	General.....	234
G.2	Overview of Dense-Interrogator channelised signalling (informative).....	234

Annex H (informative) Interrogator-to-Tag link modulation	237
H.1 Baseband waveforms, modulated RF, and detected waveforms	237
Annex I (normative) Error codes	239
I.1 Tag error codes and their usage	239
Annex J (normative) Slot counter	241
J.1 Slot-counter operation	241
Annex K (informative) Example data-flow exchange	242
K.1 Overview of the data-flow exchange	242
K.2 Tag memory contents and lock-field values	242
K.3 Data-flow exchange and command sequence	243
Annex L (informative) Optional Tag features	244
L.1 General	244
L.2 Optional Tag passwords	244
L.2.1 Kill password	244
L.2.2 Access password	244
L.3 Optional Tag memory banks and memory-bank sizes	244
L.3.1 Reserved memory	244
L.3.2 UII memory	244
L.3.3 TID memory	244
L.3.4 User memory	244
L.4 Optional Tag commands	245
L.5 Optional Tag error-code reporting format	245
L.6 Optional Tag backscatter modulation format	245
L.7 Optional Tag functionality	245
Annex M (informative) Battery Assisted Tag to Interrogator synchronization	246
M.1 Introduction	246
M.2 General concept	246
M.3 Tag to Interrogator synchronization	247
Annex N (normative) Simple Sensors Data Block	249
N.1 Simple sensor types	249
N.2 General bit-based rules	250
N.3 Temperature sensor with 14° C span	250
N.3.1 Monitored measurement span	250
N.3.2 Accuracy	251
N.3.3 Sampling regime	251
N.3.4 High in-range limit level	251
N.3.5 Low in-range limit level	252
N.3.6 Monitor delay	252
N.3.7 High out-of-range alarm delay	253
N.3.8 Low out-of-range alarm delay	253
N.3.9 Alarms	254
N.4 Temperature sensor with 28° C span	255
N.4.1 Monitored measurement span	255
N.4.2 Accuracy	255
N.4.3 Sampling regime	255
N.4.4 High in-range limit	255
N.4.5 Low in-range limit	255
N.4.6 Monitor delay	256
N.4.7 High out-of-range alarm delay	256
N.4.8 Low out-of-range alarm delay	256
N.4.9 Alarms	256
N.5 Relative humidity	256
N.5.1 Monitored measurement span	256
N.5.2 Accuracy	256
N.5.3 Sampling regime	257
N.5.4 High in-range limit level	257
N.5.5 Low in-range limit level	257

N.5.6	Monitor delay	257
N.5.7	High out-of-range alarm delay	257
N.5.8	Low out-of-range alarm delay	257
N.5.9	Alarms.....	257
N.6	Impact	258
N.6.1	Monitored measurement span	258
N.6.2	Accuracy	258
N.6.3	Sampling regime.....	258
N.6.4	High in-range limit	258
N.6.5	Low in-range limit.....	258
N.6.6	Monitor delay	258
N.6.7	High out-of-range alarm delay	258
N.6.8	Low out-of-range alarm delay	259
N.6.9	Alarms.....	259
N.7	Tilt	259
N.7.1	Monitored measurement span	259
N.7.2	Accuracy	259
N.7.3	Sampling regime.....	259
N.7.4	High in-range limit	259
N.7.5	Low in-range limit.....	259
N.7.6	Monitor delay	259
N.7.7	High out-of-range alarm delay	260
N.7.8	Low out-of-range alarm delay	260
N.7.9	Alarms.....	260
Annex O	(normative) Record structures and commands for Ported Simple Sensors	261
O.1	Record structure types	261
O.1.1	Simple sensor data block	261
O.1.2	Sensor characteristics record block	262
O.1.3	Manufacturer record block	262
O.1.4	Authorisation password record block.....	263
O.1.5	Calibration record block	263
O.1.6	Sample and configuration record block.....	265
O.1.7	Event record block	266
O.1.8	Time synchronisation record block.....	267
O.2	Ported Simple Sensor commands	267
O.2.1	Read-Simple-Sensor-Data-Block	267
O.2.2	Read-Manufacturer-Record	268
O.2.3	Write-Password	268
O.2.4	Read-Calibration-Record	269
O.2.5	Write-Sample-And-Configuration-Record.....	269
O.2.6	Initialise-Sensor-Monitoring	270
O.2.7	Read-Sample-And-Configuration-Record	271
O.2.8	Read-Event-Record	271
O.2.9	Write-UTC-Timestamp.....	272
O.2.10	Read-Time-Synchronisation-Record	273
O.2.11	Erase-Monitored-Data	274
O.2.12	Activate-Simple-Sensor	274
O.2.13	Deactivate-Simple-Sensor	275
Annex P	(informative) BAP PIE and Manchester mode tutorial guide.....	276
P.1	Executive summary of Battery Assisted Passive RFID in this standard.....	276
P.2	Battery Assisted Passive fundamentals	278
P.2.1	Propagation physics and resulting relationship between Interrogator and Tag sensitivity	278
P.2.2	Tag receiver issues	280
P.3	BAP PIE	281
P.4	Manchester.....	281
P.5	Guidance on using Next vs. Deactivate_BAT (PIE and Manchester).....	282
P.6	Reliable inventory status tracking.....	282
P.7	Environmental validation.....	283
P.7.1	INACT_T and (Selective) Global Timeout timer refresh	283

P.8	Fade delay tolerance via INACT_T and Global Timeout	284
P.9	Clocks and commanded data rates and BLFs	284
P.10	Tag Capabilities Reporting and Setting (TCRS)	285
P.11	BAP PIE persistence compliance.....	285
Annex Q	(informative) Manchester mode RF power control.....	286
Q.1	General.....	286
Q.2	Power levelling description	286
Q.3	Power leveling algorithm	288
Bibliography		291

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

ISO/IEC 18000-63 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

ISO/IEC 18000 consists of the following parts, under the general title *Information technology — Radio frequency identification for item management*:

- *Part 1: Reference architecture and definition of parameters to be standardized*
- *Part 2: Parameters for air interface communications below 135 kHz*
- *Part 3: Parameters for air interface communications at 13,56 MHz*
- *Part 4: Parameters for air interface communications at 2,45 GHz*
- *Part 6: Parameters for air interface communications at 860 MHz to 960 MHz General*
- *Part 61: Parameters for air interface communications at 860 MHz to 960 MHz Type A*
- *Part 62: Parameters for air interface communications at 860 MHz to 960 MHz Type B*
- *Part 63: Parameters for air interface communications at 860 MHz to 960 MHz Type C*
- *Part 64: Parameters for air interface communications at 860 MHz to 960 MHz Type D*
- *Part 7: Parameters for active air interface communications at 433 MHz*

Introduction

This part of ISO/IEC 18000 describes a passive backscatter radio frequency identification (RFID) system that supports the following system capabilities:

- identification and communication with multiple tags in the field;
- selection of a subgroup of tags for identification or with which to communicate;
- reading from and writing to or rewriting data many times to individual tags;
- user-controlled permanently lockable memory;
- data integrity protection;
- Interrogator-to-tag communications link with error detection;
- tag-to-Interrogator communications link with error detection;
- support for both passive back-scatter tags with or without batteries.

This part of ISO/IEC 18000 specifies the physical and logical requirements for a passive-backscatter, RFID system operating in the 860 MHz to 960 MHz frequency range. The system comprises Interrogators, also known as readers, and tags, also known as labels.

An Interrogator transmits information to a tag by modulating an RF signal in the 860 MHz to 960 MHz frequency range. The tag receives both information and operating energy from this RF signal. Passive tags are those which receive all of their operating energy from the Interrogator's RF waveform. If tags maintain a battery then they may operate using some passive principles; however, they do not necessarily get all their operating energy from the Interrogator's RF waveform.

An Interrogator receives information from a tag by transmitting a continuous-wave (CW) RF signal to the tag; the tag responds by modulating the reflection coefficient of its antenna, thereby backscattering an information signal to the Interrogator. The system is Interrogator-Talks-First (ITF), meaning that a tag modulates its antenna reflection coefficient with an information signal only after being directed to do so by an Interrogator.

Interrogators and tags are not required to talk simultaneously; rather, communications are half-duplex, meaning that Interrogators talk and tags listen, or vice versa.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning radio frequency identification technology.

ISO and IEC take no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured ISO and IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with ISO and IEC.

Information on the declared patents may be obtained from:

Contact details	
Patent Holder:	
Legal Name	Atmel Automotive GmbH
Contact for license application:	
Name & Department	Leo Merken, Legal Department, ATMEL Corporation
Address	2325 Orchard Parkway
Address	San Jose, CA 95131 USA
Tel.	+1 408 436 4251
Fax	+1 408 487 2615
E-mail	leo.merken@atmel.com
URL (optional)	
Patent Holder:	
Legal Name	CISC Semiconductor Design+Consulting GmbH
Contact for license application:	
Name & Department	Markus Pistauer, CEO
Address	Lakeside B07
Address	9020 Klagenfurt, Austria
Tel.	+43(463) 508 808
Fax	+43(463) 508 808-18
E-mail	m.pistauer@cisc.at
URL (optional)	www.cisc.at

Patent holder:

ETRI (Electronics Telecommunication Research Institute)

Contact for license application:

Name & Department: Min-Sheo Choi, Intellectual Property Management Team

Address: 138 Gajeongno, Yuseong-gu

Address: Daejeon, 305-700, Korea

Tel. +82-42-860-0756

Fax +82-42-860-3831

E-mail choims@etri.re.krURL (optional) www.etri.re.kr**Patent Holder:**

Legal Name Impinj, Inc.

Contact for license application:

Name & Department Chris Diorio, CTO

Address 701 N. 34th Street, Suite 300

Address Seattle, WA 98103, USA

Tel. +1.206 834 1115

Fax +1.206 517.5262

E-mail diorio@impinj.comURL (optional) www.impinj.com

Patent Holder:

Legal Name: Magellan Technology Pty. Limited

Contact for license application:

Name & Department: Ms Jean Angus

Address: 65 Johnston St

Address: Annandale, NSW 2038, Australia

Tel. +61 2 9562 9800

Fax +61 2 9518 7620

E-mail: license@magellan-technology.com

URL (optional): www.magellan-technology.com

Patent Holder:

Legal Name NXP B.V.

Contact for license application:

Name & Department Aaron Waxler – IP Licensing & Claims

Address 411 East Plumeria,

Address San Jose, CA 95134-1924, USA

Tel. +1 914 860-4296

Fax

E-mail Aaron.Waxler@nxp.com

URL (optional)

Patent Holder:

Legal Name TAGSYS SAS

Contact for license application:

Name & Department Mr. Alain Fanet President

Address 785 Voie Antiope, TI Athélia 3

Address F-13600 La Ciotat

Tel. +33 332188900

Fax +33 332188900

E-mail alain.fanet@tagsysrfid.comURL (optional) www.tagsysrfid.com

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The latest information on IP that may be applicable to this part of ISO/IEC 18000 can be found at www.iso.org/patents

Information technology — Radio frequency identification for item management —

Part 63:

Parameters for air interface communications at 860 MHz to 960 MHz Type C

1 Scope

This part of ISO/IEC 18000 defines the air interface for radio frequency identification (RFID) devices operating in the 860 MHz to 960 MHz Industrial, Scientific, and Medical (ISM) band used in item management applications. It provides a common technical specification for RFID devices that can be used by ISO committees developing RFID application standards. This part of ISO/IEC 18000 is intended to allow for compatibility and to encourage inter-operability of products for the growing RFID market in the international marketplace. It defines the forward and return link parameters for technical attributes including, but not limited to, operating frequency, operating channel accuracy, occupied channel bandwidth, maximum effective isotropic radiated power (EIRP), spurious emissions, modulation, duty cycle, data coding, bit rate, bit rate accuracy, bit transmission order, and, where appropriate, operating channels, frequency hop rate, hop sequence, spreading sequence, and chip rate. It further defines the communications protocol used in the air interface.

This part of ISO/IEC 18000 specifies the physical and logical requirements for a passive-backscatter, Interrogator-Talks-First (ITF) systems. The system comprises Interrogators, also known as readers, and tags, also known as labels. An Interrogator receives information from a tag by transmitting a continuous-wave (CW) RF signal to the tag; the tag responds by modulating the reflection coefficient of its antenna, thereby backscattering an information signal to the Interrogator. The system is ITF, meaning that a tag modulates its antenna reflection coefficient with an information signal only after being directed to do so by an Interrogator.

In detail, this part of ISO/IEC 18000 contains Type C.

Type C uses PIE in the forward link and a random slotted collision-arbitration algorithm.

This part of ISO/IEC 18000 specifies

- physical interactions (the signalling layer of the communication link) between Interrogators and tags,
- Interrogator and tag operating procedures and commands,
- the collision arbitration scheme used to identify a specific tag in a multiple-tag environment.

2 Conformance

To claim conformance with this part of ISO/IEC 18000, an Interrogator or tag shall comply with all relevant clauses of this part of ISO/IEC 18000, except those marked as “optional”. The Interrogator or tag shall also operate within local radio regulations, which can further restrict operation.

Relevant conformance test methods are provided in ISO/IEC TR 18047-6.

Conformance can also require a license from the owner of any intellectual property utilized by said device.

2.1 Interrogator conformance and obligations

To conform to this part of ISO/IEC 18000, an Interrogator shall

- support Type C
- implement the mandatory commands defined in this part of ISO/IEC 18000;
- modulate/transmit and receive/demodulate a sufficient set of the electrical signals defined in the signalling layer of this part of ISO/IEC 18000 to communicate with conformant tags; and
- operate within the applicable local regulations.

To conform to this part of ISO/IEC 18000, an Interrogator may

- implement any subset of the optional commands defined in this part of ISO/IEC 18000, and
- implement any proprietary and/or custom commands in conformance with this part of ISO/IEC 18000.

To conform to this part of ISO/IEC 18000, the Interrogator shall not

- implement any command that conflicts with this part of ISO/IEC 18000 or any of the parts 61, 62 and 64, or
- require the use of an optional, proprietary, or custom command to meet the requirements of this part of ISO/IEC 18000.

2.2 Tag conformance and obligations

To conform to this part of ISO/IEC 18000, a tag shall:

- support Type C;
- operate over the frequency range from 860 MHz to 960 MHz, inclusive;
- implement the mandatory commands defined in this part of ISO/IEC 18000 for the supported types;
- modulate a backscatter signal only after receiving the requisite command from an Interrogator; and
- conform to local radio regulations.

To conform to this part of ISO/IEC 18000, a tag may

- implement any subset of the optional commands defined in this part of ISO/IEC 18000; and
- implement any proprietary and/or custom commands as defined in Clauses 7.

To conform to this part of ISO/IEC 18000, a tag shall not:

- implement any command that conflicts with this part of ISO/IEC 18000 or any of the parts 61, 62 and 64;
- require the use of an optional, proprietary, or custom command to meet the requirements of this part of ISO/IEC 18000; or
- modulate a backscatter signal unless commanded to do so by an Interrogator using the signalling layer defined in this part of ISO/IEC 18000.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7816-6, *Identification cards — Integrated circuit cards — Part 6: Interindustry data elements for interchange*

ISO/IEC 15961, *Information technology — Radio frequency identification (RFID) for item management — Data protocol: application interface*

ISO/IEC 15962, *Information technology — Radio frequency identification (RFID) for item management — Data protocol: data encoding rules and logical memory functions*

ISO/IEC 15963, *Information technology — Radio frequency identification for item management — Unique identification for RF tags*

ISO/IEC 19762 (all parts), *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary*

EPCglobal Tag Data Standards version 1.3 and above, EPCglobal Inc.